CANEPA & CAMPI SINCE1901
LIFE SAVING EQUIPMENT

INFLATABLE
LIFEJACKET

The particular design thanks to the smallest dimensions and the great dressability is the ideal in order to work in emergency Size: adult kg. 43 or more and height cm. 155 or more. Cover in Cordura. Buoyancy through a chamber in Polyamide Fabric TPU-coated welded. Double compartment splitted by a PU membrane. Twin chamber. Spray Hood including.

ORIONE HDLP 275 N — Cod. L0160R24-HDLP

Hazardous Duty Lifejacket Preserver (automatic type)
Triple activation system
Manual, oral and automatic activation.
Colour: velise navy blue, stole yellow
Adults size with weight equal to or more than 43 kg., height equal or more 155 cm., chest girth up to 175 cm.
Weight Kg. 1,5 (approx)
Buoyancy chamber: TPU coated nylon welded
Buoyancy 18 kg (approx)
Chamber: twin chamber, polyamide fabric TPU coated
Inflation: primary compartment can be automatic/manually/orally inflated; secondary compartment can be orally inflated only
Gas charge: 60 grams CO^2
Retro riflective trim: 250 cm^2 retro reflective applied on spray hood, 400 cm^2 retro reflective applied on buoyancy chamber
Miscellaneous:
- SOLAS approved water activated light.
- Spray hood with transparent visor
- Tensile strength of waist belt 200-300 kg
- Whistle
- Rescue stop
- User's guide/instruction
- Buddy line with toggle
- Steel buckle

Canepa & Campi S.r.l. - Via Gramsci, 4 – Manesseno (GE) ITALY
phone +39 010 726 1006 - mail: rcampi@canepaecampi.com
www.canepaecampi.com

CANEPA & CAMPI SINCE1901
LIFE SAVING EQUIPMENT

founded in 1901, market leader in the production and distribution of lifesaving equipment, has developed a worldwide network of reliable distributors. The company is in the maker's lists of the main international Shipyards, Cruising and Cargo Companies, Military Navy, Oil and Gas Companies, being one of the main players in the market for foam and inflatable lifejackets, immersion suits, lights and other safety items supplies.

ORIONE POUCH 150 N

Automatic Inflatable Lifejacket type — Cod. L0160R04P
Manual Inflatable Lifejacket type — Cod. L0160R04P-M
Manual and automatic activation.
Colour: pouch navy blue, chamber orange, spray hood orange
Adults size with weight equal to or more than 43 kg., height equal or more 155 cm., chest girth up to 175 cm.
Dimensions: weist worm 22x16x8 cm (approx), neck worm 55x30 cm (approx)
Weight Kg. 1,250 (approx)
Buoyancy chamber: TPU coated nylon welded
Buoyancy 18 kg (approx)
Cover: navy blue, corduroy 280 g/m^2
Chamber: two orange colour, polyamide fabric TPU coated
Inflation: primary compartment can be manually or orally inflated; secondary compartment only orally inflated
Gas charge: cylinder, 30/33 grams CO^2
Retro riflective trim: 2 pcs. 100x50 mm retro reflective trim applied on spray hood, 4 pcs. 100x50 retro reflective trim applied on buoyancy chamber
Miscellaneous:
- SOLAS approved water activated light.
- Whistle
- Buddy line 1200 mm (approx)
- Spray hood
- Packed in a pouch
- Tensile strength of waist belt 200-300 kg
- Lenght of waist belt approx. 140 cm

LIFEJACKETS LIGHTS

C&C LIGHT 01 automatic

IMPA CODE N. 330143

Cod. L0170M01

It is automatically activated when it is dropped in the water and the sensors on batteries body come in contact with water. Once activated, it works with the operating sequence "FLASHING-STEADY-SOS-OFF" by the manual switch. Because of its multifunction, it can be used not only as indicating-position light for various lifejackets, but also as an emergency signal for different outdoor sports. The light can be seen clearly from at least 1.5 km in 360° directions so that it can increase the success of rescue operations. This lifejacket light is anti-UV and corrosion resistant. The clip makes installation easy and firm. Activation: water activation automatically on / manual off manual on / manually change function. Performance: fire-resistant, oil-resistant, mould-proof, corrosion-proof, water-proof. Environment Performance: meet RoHS and asbestos free requirements. 2 AAA alkaline batteries. SMT White LED light. Function: flashing – steady – SOS – OFF. Flash frequency 50~70 times/min. Luminous intensity >0.75 cd. Operation life approx. 8 h over 0,75 cd. Storing temperature - 1° C ~ + 30° C. Expiry Date 5 years. Dimensions mm. 62,5 x 25,4 x 23,5. Weight 38 g (including clip).8.
Approved according Solas 74(83) Directive (MED) 2014/90/EU; MED/1.2c;USCG Category N° 161.112;Transport Canada TP14425E and TP14612E.



Canepa & Campi S.r.l. - Via Gramsci, 4 – Manesseno (GE) ITALY
phone +39 010 726 1006 - mail: rcampi@canepaecampi.com
www.canepaecampi.com